



COMBI GREENSPIRIT II MK

Technical information

DIMENSIONS	L.960 x l.236 x h.223 mm
SPREADING DISTANCE	360 mm
SPREADING FORCE	36 - 783 kN
OPENING WIDTH	285 mm
PULLING WIDTH	440 mm
MAXIMUM PULLING FORCE	53 kN
WEIGHT (WITH BATTERY)	18,4 kg
NOMINAL PRESSURE	700 bar
EN 13204 CLASS	CK36/360I-18,4
CUTTING POWER ACCORDING TO EN 13204	1I-2K-3J-4K-5J
NFPA CUTTING CLASS	A7-B8-C7-D9-E8-F5

Characteristics

ROBUSTNESS and SAFETY

- Reinforced composite casing
- Removable waterproof cover for a complete protection of the battery
- Forged steel blades for better cutting performance and an extended resistance.
- 4 LED lights to illuminate the cutting area
- Control handle far away from the On/Off switch for an optimal security

ERGONOMIC and AUTONOMOUS

- Compact, light and balance
- Compatible with M18 battery (or via an adapter with the M28, as well as with other commercially available batteries upon request)
- Same battery on all tools
- Battery available at all Milwaukee dealer

EASE OF USE

- Intuitive ON/OFF switch with built in light
- Unsymmetrical control handle for an easier recognition of the cutting direction
- Easy and quick battery insertion and replacement
- 360° fixed handle for a quick use in any position

MADE IN FRANCE

COMPATIBLE WITH M18 & M28 BATTERIES



Accessories

- Battery Li-ion 18V, 8Ah
- 220V Charger
- Power supply
- Transport bag
- M18 to M28 Scorpe Technologies battery adapter
- Mechanical extension of 740mm
- Set of chains
- Pulling device



Option

- Waterproof cover



Sales service :
+33 (0)3 24 73 00 08

After Sales :
sav@scorpe.eu
+33 (0)3 24 73 00 02