



COMBI GREENSPIRIT II SK

Technical information

DIMENSIONS	L.804 x l.236 x h.223 mm
SPREADING DISTANCE	270 mm
SPREADING FORCE	31 - 591 kN
OPENING WIDTH	395 mm
MAXIMUM PULLING FORCE	36 k N
WEIGHT (WITHOUT BATTERY)	14,04 kg
WEIGHT (WITH BATTERY)	15,10 kg
NOMINAL PRESSURE	700 bar
EN 13204 CLASS	BK3/1/270D-15,1
CUTTING POWER EN 13204	1E-2E-3E-4D-5F
NFPA CUTTING CLASS	A5-B4-C5-D5-E4-F3

Characteristics

ROBUSTNESS and SAFETY

••••

- Reinforced composite casing
- Removable waterproof cover for a complete protection of the battery
- Forged steel blades for better cutting performance and an extended resistance.
- 4 LED lights to illuminate the cutting area
- Control handle far away from the On/Off switch for an optimal security

ERGONOMIC and AUTONOMOUS

••••

- Compact, light and balance
- Compatible with M18 battery (or via an adapter with the M28, as well as with other commercially available batteries upon request)
- Same battery on all tools
- Battery available at all Milwaukee dealer

EASE OF USE

••••

- Intuitive ON/OFF switch with built in light
- Unsymmetrical control handle for an easier recognition of the cutting direction
- Easy and quick battery insertion and replacement
- 360° fixed handle for a quick use in any position

MADE IN FRANCE

COMPATIBLE WITH M18 & M28 BATTERIES



Options

- Battery Li-ion 18V, 8Ah
- 220V Charger
- Power supply
- Transport bag
- M18 to M28 Scorpe Technologies battery adapter



Option

- Waterproof cover



Sales service :
+33(0)3247300 08

After Sales :
sav@scorpe.eu
+33 (0)3 24 73 00 02